



LSK 960 Manchet til TERRA/OPPTIRIB og PRAGMARØR - for tilslutning på beton

(direkte tilslutning uden brug af overgang)

VVS nummer	Rør dimension	Borehul dimension	Beskrivelse
192776.200	200	226	Materiale: SBR gummi *= NBR (olieressistent) lht. EN 681-1
192776.250	250	276	
192776.315	315	341	
192776.400	400	426	
192776.500	500	526	
192776.630	630	656	
192776.201*	200	226	
192776.251*	250	276	
192776.316*	315	341	
192776.401*	400	426	
192776.501*	500	526	
192776.631*	630	656	


LSK 960 Manchet til ULTRA 1 - for tilslutning på beton

(direkte tilslutning uden brug af overgang)

VVS nummer	Rør dimension	Borehul dimension	Beskrivelse
192777.200	200	226	Materiale: SBR gummi *=NBR (olieressistent) Leveres med indlæg
192777.250	250	276	
192777.315	315	341	
192777.400	400	426	
192777.560	560	586	
192777.201*	200	226	
192777.251*	250	276	
192777.316*	315	341	
192777.401*	400	426	
192777.561*	560	586	

LSK 960 Manchet til ULTRA 2 - for tilslutning på beton

(direkte tilslutning uden brug af overgang)

VVS nummer	Rør dimension	Borehul dimension	Beskrivelse
192779.200	200	226	Materiale: SBR gummi *= NBR (olieressistent) Leveres med indlæg
192779.250	250	276	
192779.315	315	341	
192779.450	450	476	
192779.560	560	586	
192779.201*	200	226	
192779.251*	250	276	
192779.316*	315	341	
192779.451*	450	476	
192779.561*	560	586	

Montagevejledning Type LSK 960

KORRUGEREDE RØR
TERRA/OPPTIRIB OG PRAGMA



ULTRA 1 & ULTRA 2



Tolerance borehul: +/- 1mm.

**Manchet til korrugerede rør - ultra 1 & 2
Montage, betjenings og vedligeholdelsesvejledning**